



Installation requirements

Connectivity:	Internet connection:	Either password protected 2.4 GHz / 5 GHz Wi-Fi network or Ethernet. NB: Ethernet is a factory added option, additional charges for installation may apply. It is not possible to use Wi-Fi as connection method after the shower has been prepared for Ethernet.
Electrical Supply:	Residual circuit breaker:	One breaker per Shower Core
	Power supply:	One Phase, 240 VAC / 50 Hz / 16 A
	Mains supply wire:	Min. 2.5 mm ² (rated for 16 A circuit)
Plumbing / Water:	Incoming water supply connections:	Separate hot and cold, 2x female G 1/2" swivel nut
	Incoming cold water temperature (min-max):	4-25 °C
	Incoming hot water temperature (min-max):	50-65 °C
	Incoming water pressure (min-max):	2-10 bar. The supply pressure is the fundamental requirement for the shower flow: <ul style="list-style-type: none">• 2 bar: 7.5 liter/min• 3 bar: 9.5 liter/min• 4 bar: 11.0 liter/min
	Recommended water supply flow:	9 liter/min per inlet hot and cold
	Water hardness (min-max):	Minimum: 3-10 °dH Recommended: 6-10 °dH (or a total hardness of 110-180 mg CaCO ₃ /litre)
	Water iron content:	<0.3 mg/litre

ORBITAL SYSTEMS

For further information please visit www.orbital-systems.com